

3M™ Value Duct Tape 1900



Economical Choice

Sealing, holding, and marking

Add cost-effective 3M™ Value Duct Tape 1900 to every tool box and job site for a variety of light duty applications.

- Silver polyethylene backing over a cloth scrim resists moisture for reliable tape performance in moist or humid environments
- Synthetic rubber pressure sensitive adhesive sticks on contact to metal, glass, plastic, concrete, and other surfaces in non-critical applications
- Surface readily accepts writing with markers for temporary labeling
- Tape tears easily by hand from the roll
- Individually wrapped roll for easy identification and to keep the roll clean until ready for use



Product Information

| Product | Color | Tape Structure (Backing/Adhesive) | Total Thickness mills (mm) | Adhesion to Steel oz/in width N/100mm | Tensile Strength lb/in (N/100mm) | Elon-gation | Size | Packaging | Rolls/ Case | Cases/ Pallet | UPC 00-050005- |
|---------|--------|--|----------------------------|---------------------------------------|----------------------------------|-------------|---------------------------------|-----------------|-------------|---------------|----------------|
| 1900 | Silver | Polyethylene over cloth scrim/synthetic rubber | 5.8 (0.147) | 58 (63.5) | 16 (280.2) | 12% | 1.88 in x 50 yd (48mm x 45.7 m) | Individual Wrap | 24 | 60 | 23421-7 |
| | | | | | | | 2.83 in x 50 yd (72mm x 45.7 m) | | 12 | 72 | 23422-4 |



Value priced for light duty jobs.

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

WARRANTY AND LIMITED REMEDY: 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to repair or replace the product or refund the purchase price. **LIMITATION OF LIABILITY:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center Bldg. 21-1W-10
900 Bush Ave.
St. Paul, MN 55144
1-800-362-3550
www.3M.com/industrialtapes

3M is a trademark of 3M Company.

Printed in U.S.A.
© 2007 3M
70-0711-0174-8